



Series 6

VU226LD

22" LCD HD Ready with Stand Rotation / Steam Moulding (Black Gloss)



VU226LD

Series 6

22" LCD HD Ready with Stand Rotation / Steam Moulding Finish

Features

Widescreen Aspect Ratio

1366 (H) x 768 (V) pixel resolution:

High resolution pixel density with built-in image scaler to handle inputs from a variety of digital and analogue audio/ video source.

170°(H)/160°(V) Viewing Angle

Improves viewing angle, contrast, and brightness to provide an even better picture.

10000:1 < Dynamic Contrast Ratio/ 350Cd/m² Brightness: As two of the most important determining factors in overall Picture quality, contrast and brightness levels achieve new heights in this latest generation LCD panel. Videocon's new LCD TV's give the most stunning realistic picture quality ever from a flat panel set.

Response time: Fast 5ms response time minimizes blurring of moving video.

Multilingual on-screen displays (22) English, French, German, Spanish, Italian, Netherlands, Portuguese, Turkish, Polish, Croatian, Norwegian, Swedish, Hungarian, Danish, Finnish, Czech, Rumanian, Slovenian, Bulgarian, Russian, Greek, Serbian.

Connections

A/V inputs: 1

HDMI In: 1

SCART: 1

Component input: 1

PC audio / Video input: 1 / 1

CI Slot input: 1

S-Video input: 1

Headphone out: 1

USB Slot: 1 (Playback Only - jpeg/ mpeg/ mp3 media files)

Specifications

Panel: Wide (16:9) LCD

TV system: PAL / SECAM / NTSC in AV Playback

DVB Terrestrial TV and Radio reception

Tuner preset channel: 200 in ATV / 999 in DTV pre-selected

Antenna: 75-ohm, IEC-type

Watts per channel: 3W RMS x 2

Shipping information (LxWxH)

Dimensions: 538 x 180 x 401 mm

Weight: 7,4 Kg

Order code VU226LD

EAN Code 8033406862974

VIDEOCON 

EAN CODE**8033406862974****PANEL RELATED**

| | |
|---------------------------------------|---------------------------------|
| Screen Size | 21.6" |
| Aspect Ratio | 16:9 |
| Resolution | 1366 x 768 |
| Display Colors | 16,7 Million |
| Dynamic Contrast Ratio | 10,000:1 |
| Brightness (cd/m2) | 350 |
| Fast Response Time | 5ms |
| Backlight Life (hr) | 50,000 |
| Viewing Angle (°) | 170 /160 |
| HD Status | HD Ready |
| Number of Prog TV : Analogue /Digital | 200 / 999 |
| DVB-T Free on Air | ● |
| Receiving /Color System | PAL /SECAM /NTSC in AV playback |

PICTURE

| | |
|--------------------------------------|---------------------------------------|
| Film-Mode Detection | ● |
| DCDI | ● |
| DCRe (Digital Colour Reality Engine) | ● |
| Sel Pict Modes | Standard / Dynamic / Movie / Personal |
| Picture Scale / Zoom | Auto /Zoom 1 /Zoom 2 /4:3 |
| Color Temperature | Warm /Cool /Normal /Personal |
| Brightness /Contrast /Color Control | ● |
| Sharpness Control | ● |
| Tint Control (Only NTSC System) | ● |
| Picture Improve | — |
| Video Noise Reduction (DNR) | ● |
| White Peak Limiter | ● |
| Black Stretch | ● |
| Blue Stretch | ● |

AUDIO

| | |
|----------------------------|------------------------------------------|
| Audio OUT (RMS) | 2 x 3W |
| Sound System | I /BG /DK /L /L' |
| Sel Sound Modes | Standard /Music /Movie /Sports /Personal |
| Nicam Stereo | ● |
| Woofers | — |
| Equalizer (3/5- Bands) | ● |
| Incredible Stereo | — |
| Loudness | — |
| Stereo Playback | ● |
| Auto Volume Leveller (AVL) | ● |
| Bass /Treble /Balance | ● |
| Surround | ● |

| CONNECTORS | |
|--------------------------------------------|-----------------------|
| RF Tuner (75 ohm) | ● |
| Composite (AV) Input | 1 |
| Scart | 1 |
| Pc Audio Input | 1 |
| VGA PC input (D-sub 15pin) | 1 |
| S-Video Input | 1 |
| Component (Y/Pb /Pr) Input | 1 |
| HDMI (1.3) Input | 1 |
| CI Slot | ● |
| FastCam (Pay per View Digital Terrestrial) | — |
| DVD player integrato | — |
| USB 2.0 Input (Playback Only) | 1 |
| Card Reader (3 in 1 _ SD /MMC /MS) | — |
| Headphone OUT | 1 |
| Scart Monitor OUT | ● |
| TIMER FEATURES | |
| Clock | ● |
| Clock Display | ● |
| On /Off Timer | ● |
| Auto Switch Off (No Signal) | ● |
| Reminder Timer | ● (Only DTV, Via EPG) |
| Reminder Channel | ● (Only DTV, Via EPG) |
| Sleep Timer | ● |
| CHANNEL EDIT FEATURES | |
| Channel Sorting | ● |
| Channel Move | ● |
| Channel Delete | ● |
| Channel Skip | ● |
| Program Naming | ● |
| Quick View | ● |
| Favorite Channel Accessing | ● |
| HOTEL / LOCKING MODE | |
| Hotel Mode | ● |
| Password Change | ● |
| Program Lock | ● |
| Child Lock | ● |
| Tuning Lock | ● |
| Volume Lock | ● |
| Volume Limit | ● |
| Front Panel Keys Lock | ● |
| AV Lock | ● |
| Complete Menu Lock | ● |
| Start On Program Control | ● |
| Start On Predefined Source | ● |
| Start On Predefined Channel NO. | ● |

| LANGUAGE FEATURES | |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OSD Multilanguages | 22 (English, French, German, Spanish, Italian, Netherlands, Portuguese, Turkish, Polish, Croatian, Norwegian, Swedish, Hungarian, Danish, Finnish, Czech, Rumanian, Slovenian, Bulgarian, Russian, Greek, Serbian.) |
| No. of Teletext Page | 1000 |
| Teletext level | Level 1.5 / 2.5 |
| Teletext Languages | Auto |
| Teletext Disable (In Design Menu) | • |
| OTHER FEATURES | |
| Painting | Steam Moulding |
| Stand Rotation | • |
| ACI (Automatic Channels Installation) | • |
| ATS (Automatic Channels Sorting) | • |
| EPG (Electronic Progame Guide) | • |
| PIP (Picture-in-Picture) | — |
| PARAMETRIC INFORMATION | |
| Automatic Voltage Range (AVR) | 100 - 240 V~ 50/60 Hz |
| Power Consumption Maximun | 65W |
| Power Consumption un Standby | < 1W |
| Accessory | Remote Handset /User's Guide Book /Power Cord. |
| Wall Mounting Compatibility / Vesa Standards | • (100 x 100mm) |
| LOGISTIC INFO | |
| Unit dimensions with Stand Base (L/W/H) mm | 538 x 180 x 401 |
| Unit dimensions without Stand Base (L/W/H) mm | 538 x 76 x 364 |
| Net Weight (Kg) | 5,93 |
| Box Weight (Kg) | 7,4 |
| Box Dimensions (L/W/H) mm | 585 x 525 x 153 |
| Loading qty Pallet | 56 pcs |
| Loading qty Truck | 1344 pcs |
| Loading qty 40 Ft Standard | |
| Loading qty 40 Ft HQ | |

VIDEOCON 

Note: *These specs are subject to change without notice.