



PLC-XW57

- Brightness: 2000 ANSI Lumens
- Resolution, native 1024 x 768 (XGA)
- MyLogo Function for custom logo transfer
- Key Lock Function, PIN code lock for security
- Very quiet 26dB in Eco mode
- 3 years Warranty

PLC-XW57

TECHNICAL DETAILS	PLC-XW57
Category	Business & Education
Panel	3 x 0.6" TFT p-Si (4:3), Micro lens
Lamp	200W UHP (LMP122)
Brightness ANSI lumens	2,000
Lamp Service Life	3,000 h (Eco Mode) / 2,000 h (Normal Mode)
Fan Noise	26dBA (Eco Mode) / 32dBA (Normal Mode)
Standard Lens	F= 1.65-1.83 / f=22.5-27.0mm
Throw Distance Ratio	1.78 – 2.1:1
Throw Distance	1.4-13.2m
Contrast Ratio	400:1
Resolution in pixels	1024 x 768 (XGA)
Image size min-max (diagonal)	40" – 300"
Uniformity	85%
Bandwidth/Frequency	110 MHz, horizontal 15 kHz~100 kHz, Vertical 50 Hz ~ 100Hz
Colour Systems	PAL, SECAM, NTSC, NTSC4.43. PAL-M/N
Connections	Input 1: D-sub15 (Analog RGB, Component, S-Video), Mini Jack (Audio Input) Input 2: D-sub15 (Analog RGB, Monitor out) Input 3: RCA x1 (Composite Video), RCA x2 (Video Audio) Control: 8 Pin mini DIN
Keystone Correction	vertical +/- 20°
Up/Down Ratio	6 : 1
HDTV Signals	1080i/50, 1080i/60, 1035, 720p
Computer Compatibility	UXGA / WXGA / SXGA+ / SXGA / XGA / SVGA / VGA / MAC
Zoom/Focus	1.2 X / Manual
Power Consumption/Voltage	200 w (Eco mode), 240W (normal mode), 9 W (Stand By)
Warranty	3 years
Dimensions (W x H x D)	330 x 97.9 x 237 mm
Weight	2.9 kg
Standard Accessories	Remote Control, Power Cable, Owners Manual (CD Rom), Computer Cable (D-sub15-Dsub15)
Optional Accessories	POA-MCSRL (Serial control Cable), POA-CA-SCART (Scart – D-sub15)
Lenses	Standard lens

* You can use the distance calculator at www.sanyo.co.uk to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 09/2007



Telephone: 01923 246363

Email: info@sanyo.co.uk

Visit: www.sanyo.co.uk